

Pad Mount Transformer

1548

1	OIL	☒	DRY	☐	NEW	☐	USED	☐	REBUILT	☐	RENTAL	☐	
2	KVA	500			IMPEDANCE	5.45 %			TEMP RISE	65 °			
3	1 PHASE	☐	2 PHASE	☐	3 PHASE	☒			3 Ø TO 2 Ø	☐			
4	HIGH VOLTAGE BUSHINGS	1	☐	2	☐	3	☒			4	☐	#	☐
	LOW VOLTAGE BUSHINGS	1	☐	2	☐	3	☐			4	☒	#	☐
5	MAKE	General Electric						CAT #					
6	SERIAL #	Q572141-TWS						STYLE #					
7	PRIMARY VOLTAGE	12470											
8	PRIMARY CONNECTION	WYE		☐	DELTA		☒ (3 Ø ONLY)						
9	PRIMARY TAPS	1-A	13094			2-B	12785			3-C	12470		
		4-D	12158			5-E	11847			6-F			
										7-G			
10	SECONDARY VOLTAGE	120y/208											
11	SECONDARY CONNECTION	WYE		☒	DELTA		☐ (3 Ø ONLY)						
12	TYPE OF FLUID	OIL	☒	R TEMP	☐	FR3	☐	SILICONE	☐				
13	GALLONS OF FLUID	260											
14	DOES TRANSFORMER HAVE ANY SWITCHING:												
14 A	OPEN/CLOSE SWITCH	YES	☐	NO	☒								
14 B	TAP CHANGER SWITCH	YES	☒	NO	☐								
	OUTSIDE TRANS TANK	YES	☒	NO	☐								
14 C	DUAL VOLTAGE SWITCH	YES	☐	NO	☒								
	OUTSIDE TRANS TANK	YES	☐	NO	☒								
14 D	DELTA-WYE SWITCH	YES	☐	NO	☒								
14 E	HIGH VOLTAGE FUSED	YES	☐	NO	☒								
	TYPE FUSE/MAKE							CAT #					
	AMP RATING												
	DRY WELL	☐	BAYONET	☐	CLIP MTD	☐	ARC STRANGLER	☐					
15	PRIMARY IS	LIVE FRONT	☒										
	DEAD FRONT	☐											
	IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:												
	YES	☐	NO	☐	LIVE CONVERSION	☐	ARRESTORS	☐					
					DEAD BREAK	☐	LOAD BREAK	☐					
16	DIMENSIONS:	96.5"	H x	78"	Wx	63.5"	D	WEIGHT	4900				
17	COMMENTS:												