

Pad Mount Transformer

2070

1 OIL  DRY  NEW  USED  REBUILT  RENTAL

2 KVA 500 IMPEDANCE 4.1 % TEMP RISE 65 °

3 1 PHASE  2 PHASE  3 PHASE  3 Ø TO 2 Ø

4 HIGH VOLTAGE BUSHINGS 1  2  3  4  #

LOW VOLTAGE BUSHINGS 1  2  3  4  #

5 MAKE Cooper CAT # 001A3V11K35A

6 SERIAL # 0650019663 STYLE # \_\_\_\_\_

7 PRIMARY VOLTAGE 12470

8 PRIMARY CONNECTION WYE  DELTA  (3 Ø ONLY)

9 PRIMARY TAPS 1-A 14400 2-B 13800 3-C 13200

4-D 12870 5-E 12470 6-F 12000 7-G 11500

10 SECONDARY VOLTAGE 240/120MT

11 SECONDARY CONNECTION WYE  DELTA  (3 Ø ONLY)

12 TYPE OF FLUID OIL  R TEMP  FR3  SILICONE

13 GALLONS OF FLUID 188

14 DOES TRANSFORMER HAVE ANY SWITCHING:

14 A OPEN/CLOSE SWITCH YES  NO

14 B TAP CHANGER SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

14 C DUAL VOLTAGE SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

14 D DELTA-WYE SWITCH YES  NO

14 E HIGH VOLTAGE FUSED YES  NO

TYPE FUSE/MAKE \_\_\_\_\_ CAT # \_\_\_\_\_

AMP RATING \_\_\_\_\_

DRY WELL  BAYONET  CLIP MTD  ARC STRANGLER

15 PRIMARY IS LIVE FRONT  DEAD FRONT

IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:

YES  NO  LIVE CONVERSION  ARRESTORS

DEAD BREAK  LOAD BREAK

16 DIMENSIONS: 53" H x 80" Wx 51" D WEIGHT 4775

17 COMMENTS: \_\_\_\_\_