

Pad Mount Transformer

2531

1	OIL	☒	DRY	☐	NEW	☒	USED	☐	REBUILT	☐	RENTAL	☐	
2	KVA	1000			IMPEDANCE	5.62 %			TEMP RISE	65 °			
3	1 PHASE	☐	2 PHASE	☐	3 PHASE	☒			3 Ø TO 2 Ø	☐			
4	HIGH VOLTAGE BUSHINGS	1	☐	2	☐	3	☒	4	☐	#	☐		
	LOW VOLTAGE BUSHINGS	1	☐	2	☐	3	☐	4	☒	#	☐		
5	MAKE	GE Prolec						CAT #					
6	SERIAL #	M09G15879						STYLE #					
7	PRIMARY VOLTAGE	4160											
8	PRIMARY CONNECTION	WYE		☐	DELTA		☒	(3 Ø ONLY)					
9	PRIMARY TAPS	1-A	4368			2-B	4264			3-C	4160		
		4-D	4056			5-E	3952			6-F			
										7-G			
10	SECONDARY VOLTAGE	208y/120											
11	SECONDARY CONNECTION	WYE		☒	DELTA		☐	(3 Ø ONLY)					
12	TYPE OF FLUID	OIL	☒	R TEMP	☐	FR3	☐	SILICONE	☐				
13	GALLONS OF FLUID	301											
14	DOES TRANSFORMER HAVE ANY SWITCHING:												
14 A	OPEN/CLOSE SWITCH	YES	☐	NO	☒								
14 B	TAP CHANGER SWITCH	YES	☒	NO	☐								
	OUTSIDE TRANS TANK	YES	☒	NO	☐								
14 C	DUAL VOLTAGE SWITCH	YES	☐	NO	☒								
	OUTSIDE TRANS TANK	YES	☐	NO	☒								
14 D	DELTA-WYE SWITCH	YES	☐	NO	☒								
14 E	HIGH VOLTAGE FUSED	YES	☐	NO	☒								
	TYPE FUSE/MAKE							CAT #					
	AMP RATING												
	DRY WELL	☐	BAYONET	☐	CLIP MTD	☐	ARC STRANGLER	☐					
15	PRIMARY IS	LIVE FRONT	☒	DEAD FRONT	☐								
	IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:												
	YES	☐	NO	☐	LIVE CONVERSION	☐	ARRESTORS	☐					
					DEAD BREAK	☐	LOAD BREAK	☐					
16	DIMENSIONS:	80"	H x	65"	Wx	77"	D	WEIGHT	8010				
17	COMMENTS:												