

Pad Mount Transformer

10367

1	OIL	☒	DRY	☐	NEW	☐	USED	☐	REBUILT	☒	RENTAL	☐
2	KVA	1000			IMPEDANCE	5.8			%	TEMP RISE	65 °	
3	1 PHASE	☐	2 PHASE	☐	3 PHASE	☒			3 Ø TO 2 Ø	☐		
4	HIGH VOLTAGE BUSHINGS	1	☐	2	☐	3	☐	4	☐	#	☐	
	LOW VOLTAGE BUSHINGS	1	☐	2	☐	3	☐	4	☒	#	☐	
5	MAKE	Cooper						CAT #				
6	SERIAL #	0650012708						STYLE #				
7	PRIMARY VOLTAGE	33000gy/19053										
8	PRIMARY CONNECTION	WYE			☒	DELTA	☐	(3 Ø ONLY)				
9	PRIMARY TAPS	1-A	34650			2-B	33830			3-C	33000	
		4-D	32180			5-E	31350			6-F		
										7-G		
10	SECONDARY VOLTAGE	480y/277										
11	SECONDARY CONNECTION	WYE			☒	DELTA	☐	(3 Ø ONLY)				
12	TYPE OF FLUID	OIL	☒	R TEMP	☐	FR3	☐	SILICONE	☐			
13	GALLONS OF FLUID	395										
14	DOES TRANSFORMER HAVE ANY SWITCHING:											
14 A	OPEN/CLOSE SWITCH	YES	☒	NO	☐							
14 B	TAP CHANGER SWITCH	YES	☒	NO	☐							
	OUTSIDE TRANS TANK	YES	☒	NO	☐							
14 C	DUAL VOLTAGE SWITCH	YES	☐	NO	☒							
	OUTSIDE TRANS TANK	YES	☐	NO	☒							
14 D	DELTA-WYE SWITCH	YES	☐	NO	☒							
14 E	HIGH VOLTAGE FUSED	YES	☒	NO	☐							
	TYPE FUSE/MAKE							CAT #				
	AMP RATING											
	DRY WELL	☐	BAYONET	☒	CLIP MTD	☐	ARC STRANGLER	☐				
15	PRIMARY IS	LIVE FRONT	☐	DEAD FRONT	☒							
	IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:											
	YES	☒	NO	☐	LIVE CONVERSION	☐	ARRESTORS	☐				
					DEAD BREAK	☐	LOAD BREAK	☐				
16	DIMENSIONS:	73.5"	H x	84"	Wx	70"	D	WEIGHT	8991			
17	COMMENTS:											