

Pad Mount Transformer

1088

1 OIL  DRY  NEW  USED  REBUILT  RENTAL

2 KVA 1500 IMPEDANCE 5.6 % TEMP RISE 65 °

3 1 PHASE  2 PHASE  3 PHASE  3 Ø TO 2 Ø

4 HIGH VOLTAGE BUSHINGS 1  2  3  4  #

LOW VOLTAGE BUSHINGS 1  2  3  4  #

5 MAKE RTE CAT # \_\_\_\_\_

6 SERIAL # 926000526 STYLE # \_\_\_\_\_

7 PRIMARY VOLTAGE 13.2y/7.62 x 34.5y/19.92

8 PRIMARY CONNECTION WYE  DELTA  (3 Ø ONLY)

9 PRIMARY TAPS 1-A 36225 2-B 35363 3-C 34500

4-D 33638 5-E 32775 6-F \_\_\_\_\_ 7-G \_\_\_\_\_

10 SECONDARY VOLTAGE 2400y/4160 x 2400

11 SECONDARY CONNECTION WYE  DELTA  (3 Ø ONLY)

12 TYPE OF FLUID OIL  R TEMP  FR3  SILICONE

13 GALLONS OF FLUID 485

14 DOES TRANSFORMER HAVE ANY SWITCHING:

14 A OPEN/CLOSE SWITCH YES  NO

14 B TAP CHANGER SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

14 C DUAL VOLTAGE SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

14 D DELTA-WYE SWITCH YES  NO

14 E HIGH VOLTAGE FUSED YES  NO

TYPE FUSE/MAKE \_\_\_\_\_ CAT # \_\_\_\_\_

AMP RATING \_\_\_\_\_

DRY WELL  BAYONET  CLIP MTD  ARC STRANGLER

15 PRIMARY IS LIVE FRONT  DEAD FRONT

IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:

YES  NO  LIVE CONVERSION  ARRESTORS

DEAD BREAK  LOAD BREAK

16 DIMENSIONS: 79" H x 78.5" Wx 95" D WEIGHT 13169

17 COMMENTS: \_\_\_\_\_