

Pad Mount Transformer

12362

1	OIL	☒	DRY	☐	NEW	☒	USED	☐	REBUILT	☐	RENTAL	☐
2	KVA	1000			IMPEDANCE	6.46		%	TEMP RISE	65 °		
3	1 PHASE	☐	2 PHASE	☐	3 PHASE	☒	3 Ø TO 2 Ø		☐			
4	HIGH VOLTAGE BUSHINGS	1	☐	2	☐	3	☐	4	☒	#	☐	
	LOW VOLTAGE BUSHINGS	1	☐	2	☐	3	☐	4	☐	#	☐	6
5	MAKE	Jiangsu Daelim Electric						CAT #				
6	SERIAL #	20639T DL231381						STYLE #				
7	PRIMARY VOLTAGE	34500grdy/19920										
8	PRIMARY CONNECTION	WYE		☒	DELTA		☐	(3 Ø ONLY)				
9	PRIMARY TAPS	1-A	36220		2-B	35360		3-C	34500			
		4-D	33640		5-E	33000		6-F	32175		7-G	31350
10	SECONDARY VOLTAGE	4160Y/2400 x 2400										
11	SECONDARY CONNECTION	WYE		☒	DELTA		☒	(3 Ø ONLY)				
12	TYPE OF FLUID	OIL	☒	R TEMP	☐	FR3	☐	SILICONE	☐			
13	GALLONS OF FLUID	405										
14	DOES TRANSFORMER HAVE ANY SWITCHING:											
14 A	OPEN/CLOSE SWITCH	YES	☒	NO	☐							
14 B	TAP CHANGER SWITCH	YES	☒	NO	☐							
	OUTSIDE TRANS TANK	YES	☒	NO	☐							
14 C	DUAL VOLTAGE SWITCH	YES	☐	NO	☒							
	OUTSIDE TRANS TANK	YES	☐	NO	☒							
14 D	DELTA-WYE SWITCH	YES	☐	NO	☒							
14 E	HIGH VOLTAGE FUSED	YES	☒	NO	☐							
	TYPE FUSE/MAKE							CAT #				
	AMP RATING											
	DRY WELL	☐	BAYONET	☒	CLIP MTD	☐	ARC STRANGLER	☐				
15	PRIMARY IS	LIVE FRONT	☒	DEAD FRONT	☐							
	IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:											
	YES	☐	NO	☐	LIVE CONVERSION	☐	ARRESTORS	☐				
					DEAD BREAK	☐	LOAD BREAK	☐				
16	DIMENSIONS:	75"	H x	89"	Wx	74.5"	D	WEIGHT	9080			