

Pad Mount Transformer

12556

1	OIL	☒	DRY	☐	NEW	☒	USED	☐	REBUILT	☐	RENTAL	☐
2	KVA	2550			IMPEDANCE	5.7		%	TEMP RISE	65 °		
3	1 PHASE	☐	2 PHASE	☐	3 PHASE	☒	3 Ø TO 2 Ø ☐					
4	HIGH VOLTAGE BUSHINGS	1	☐	2	☐	3	☐	4	☐	#	☐	
	LOW VOLTAGE BUSHINGS	1	☐	2	☐	3	☐	4	☒	#	☐	
5	MAKE	Prolec GE					CAT #					
6	SERIAL #	M23A12986					STYLE #					
7	PRIMARY VOLTAGE	13800										
8	PRIMARY CONNECTION	WYE	☐	DELTA	☒	(3 Ø ONLY)						
9	PRIMARY TAPS	1-A	14400		2-B	13800		3-C	13200			
		4-D	12470		5-E	12000		6-F				
								7-G				
10	SECONDARY VOLTAGE	480Y/277										
11	SECONDARY CONNECTION	WYE	☒	DELTA	☐	(3 Ø ONLY)						
12	TYPE OF FLUID	OIL	☒	R TEMP	☐	FR3	☐	SILICONE	☐			
13	GALLONS OF FLUID	560										
14	DOES TRANSFORMER HAVE ANY SWITCHING:											
14 A	OPEN/CLOSE SWITCH	YES	☒	NO	☐							
14 B	TAP CHANGER SWITCH	YES	☒	NO	☐							
	OUTSIDE TRANS TANK	YES	☒	NO	☐							
14 C	DUAL VOLTAGE SWITCH	YES	☐	NO	☒							
	OUTSIDE TRANS TANK	YES	☐	NO	☒							
14 D	DELTA-WYE SWITCH	YES	☐	NO	☒							
14 E	HIGH VOLTAGE FUSED	YES	☐	NO	☒							
	TYPE FUSE/MAKE						CAT #					
	AMP RATING											
	DRY WELL	☐	BAYONET	☐	CLIP MTD	☐	ARC STRANGLER	☐				
15	PRIMARY IS	LIVE FRONT	☐	DEAD FRONT	☒							
	IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:											
	YES	☒	NO	☐	LIVE CONVERSION	☐	ARRESTORS	☐				
					DEAD BREAK	☐	LOAD BREAK	☒				
16	DIMENSIONS:	83"	H x	83"	Wx	96"	D	WEIGHT	13969			