

Pad Mount Transformer 2850

1 OIL DRY NEW USED REBUILT RENTAL
2 KVA 2500 IMPEDANCE 5.7 % TEMP RISE 65 °
3 1 PHASE 2 PHASE 3 PHASE 3 Ø TO 2 Ø
4 HIGH VOLTAGE BUSHINGS 1 2 3 4 #
LOW VOLTAGE BUSHINGS 1 2 3 4 #
5 MAKE Sunbelt CAT # _____
6 SERIAL # 97J294360 STYLE # _____
7 PRIMARY VOLTAGE 33000y/19050
8 PRIMARY CONNECTION WYE DELTA (3 Ø ONLY)
9 PRIMARY TAPS 1-A 34500 2-B 33825 3-C 33000
4-D 32175 5-E 31350 6-F _____ 7-G _____
10 SECONDARY VOLTAGE 480y/277
11 SECONDARY CONNECTION WYE DELTA (3 Ø ONLY)
12 TYPE OF FLUID OIL R TEMP FR3 SILICONE
13 GALLONS OF FLUID 529
14 DOES TRANSFORMER HAVE ANY SWITCHING:
14 A OPEN/CLOSE SWITCH YES NO
14 B TAP CHANGER SWITCH YES NO
OUTSIDE TRANS TANK YES NO
14 C DUAL VOLTAGE SWITCH YES NO
OUTSIDE TRANS TANK YES NO
14 D DELTA-WYE SWITCH YES NO
14 E HIGH VOLTAGE FUSED YES NO
TYPE FUSE/MAKE _____ CAT # _____
AMP RATING _____
15 DRY WELL BAYONET CLIP MTD ARC STRANGLER
PRIMARY IS LIVE FRONT DEAD FRONT
IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:
YES NO LIVE CONVERSION ARRESTORS
DEAD BREAK LOAD BREAK
16 DIMENSIONS: 71" H x 94" W x 63" D WEIGHT 14210
17 COMMENTS: _____