

Pole Mount Transformer

1884

1 NEW  USED  REBUILT

2 BUSHINGS ARRANGED:

TOP/TOP  TOP/SIDE  SIDE/SIDE

3 KVA 25 % IMPEDANCE 2.4 TEMP RISE 85 °

4 1 PHASE  2 PHASE  3 PHASE  3Ø TO 2 Ø

5 POLARITY: ADDITIVE  SUBTRACTIVE

6 HOW MANY HV BUSHINGS: 1  2  3  4  #

HOW MANY LV BUSHINGS: 1  2  3  4  #

7 MAKE \_\_\_\_\_ RTE \_\_\_\_\_ CAT # \_\_\_\_\_

8 SERIAL # 841146672 STYLE # \_\_\_\_\_

9 PRIMARY VOLTAGE 4160/7200

PRIMARY CONNECTION: WYE  DELTA  (3 Ø ONLY)

10 PRIMARY TAPS: 1-A 4368/7560 2-B 4264/7380 3-C 4160/7200

4-D 4056/7020 5-E 3952/6840 6-F \_\_\_\_\_ 7-G \_\_\_\_\_

11 SECONDARY VOLTAGE: 120/240

12 SECONDARY CONNECTION WYE  DELTA  (3 Ø ONLY)

13 TYPE OF FLUID OIL  R TEMP  FR3  SILICONE

14 GALLONS OF FLUID 18

15 DOES TRANSFORMER HAVE ANY SWITCHING:

15 A OPEN/CLOSE SWITCH YES  NO

15 B TAP CHANGER SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

15 C DUAL VOLTAGE SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

15 D DELTA-WYE SWITCH YES  NO

DIMENSIONS: 40" H x \_\_\_\_\_ Wx 24" D WEIGHT 405lb

17 COMMENTS: \_\_\_\_\_