

Pad Mount Transformer

1542

1 OIL  DRY  NEW  USED  REBUILT  RENTAL

2 KVA 2500/3125 IMPEDANCE 6.1 % TEMP RISE 65 °

3 1 PHASE  2 PHASE  3 PHASE  3 Ø TO 2 Ø

4 HIGH VOLTAGE BUSHINGS 1  2  3  4  #

LOW VOLTAGE BUSHINGS 1  2  3  4  #

5 MAKE Howard Industries CAT # \_\_\_\_\_

6 SERIAL # 1487011101 STYLE # \_\_\_\_\_

7 PRIMARY VOLTAGE 14400 x 24912y/14400

8 PRIMARY CONNECTION WYE  DELTA  (3 Ø ONLY)

9 PRIMARY TAPS 1-A 24912/14400 2-B 23874/13800 3-C 22836/13200

4-D 22265/12870 5-E 21573/12470 6-F 20760/12000 7-G 20241/11700

10 SECONDARY VOLTAGE 480y/277

11 SECONDARY CONNECTION WYE  DELTA  (3 Ø ONLY)

12 TYPE OF FLUID OIL  R TEMP  FR3  SILICONE

13 GALLONS OF FLUID 449

14 DOES TRANSFORMER HAVE ANY SWITCHING:

14 A OPEN/CLOSE SWITCH YES  NO

14 B TAP CHANGER SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

14 C DUAL VOLTAGE SWITCH YES  NO

OUTSIDE TRANS TANK YES  NO

14 D DELTA-WYE SWITCH YES  NO

14 E HIGH VOLTAGE FUSED YES  NO

TYPE FUSE/MAKE \_\_\_\_\_ CAT # \_\_\_\_\_

AMP RATING \_\_\_\_\_

DRY WELL  BAYONET  CLIP MTD  ARC STRANGLER

15 PRIMARY IS LIVE FRONT  DEAD FRONT

IF DEAD FRONT, DO WELLS HAVE LOAD BREAK BUSHINGS IN THEM:

YES  NO  LIVE CONVERSION  ARRESTORS

DEAD BREAK  LOAD BREAK

16 DIMENSIONS: 74" H x 114" Wx 96" D WEIGHT 12113

17 COMMENTS: \_\_\_\_\_